



FEATURES:

- **EXCELLENT DURABILITY:** Unique formula provides a long lasting interior protective film finish.
- **UV PROTECTION:** Unique UV absorbers protect the logs from the sun's damaging UV rays.
- **CHEMICAL AND STAIN RESISTANT:** Robust formula resists stain and chemical discolouration, making the finish easy to clean.
- **ENVIROMENYALLY FRIENDLY:** Non-toxic.
- **FOUR SHEEN LEVELS:** CRYSTAL URETHANE is available in: Gloss, Semi-Gloss, Satin and Matte.
- **EASY TO APPLY:** CRYSTAL URETHANE can easily be applied by brush, sprayed and back brushed.
- **EASY CLEAN UP:** Soap and water clean up.

CRYSTAL URETHANE

Protects

- **ALL INTERIOR WALLS + DOORS**
- **INTERIOR WOOD FLOORS/CEILINGS**
- **INTERIOR WOOD CABINETRY**
- **INTERIOR WOOD TRIM**

Timber Pro CRYSTAL URETHANE is a premium quality waterborne acrylic urethane finish. The film-forming finish provides an exceptionally washable, chemical and stain resistant coating to all interior wood surfaces.

Enhanced qualities such as: fast dry and a low VOC. non toxic formula make it the best choice for all your interior wood coatings needs. CRYSTAL URETHANE is also an excellent clear top coat to be used over Timber Pro INTERIOR STAIN FORMULA.



DEALER STAMP

604.270.4244
timberprocoatings.ca
timberprocoatings.com



CRYSTAL URETHANE

Protects + Beautifies

Where to Use

Timber Pro CRYSTAL URETHANE can be used on all new and reconditioned interior wood surfaces. CRYSTAL URETHANE can be used as a clear interior finish on its own or as a top coat over Timber Pro INTERIOR STAIN FORMULA. CRYSTAL URETHANE can also be tinted to enhance wood tones or add colour to your wood surface. CRYSTAL URETHANE can be used for:

- Log Home Interiors
- Wood Floors
- Cabinets/Vanities
- Trim
- Wood Doors
- Stairs/Banisters/Handrails
- Tongue & Groove Wood
- Windows
- Wood Walls/Ceilings

RESTRICTIONS

- Always read and follow the "Directions for Use" instructions printed on product container/brochure
- Do not apply if moisture content of wood exceeds 15%
- Do not apply in temperatures below 10C (50F)
- Do not use steel wool to sand or smooth the surface
- Do not thin the product
- Do not shake CRYSTAL URETHANE to mix contents; stir contents only

Application

- Do a colour test before proceeding with the entire job. Apply appropriate number of coats as per surface and wood species (see "Directions for Use"); allow each coat to dry before proceeding with the next coat.
- Stir the material thoroughly before and occasionally during use.
- Application is best with a quality nylon/polyester brush or pad applicator. Airless sprayer is also an approved option to apply CRYSTAL URETHANE.
- Walls/ceilings/trim require a minimum of two coats of CRYSTAL URETHANE, doors/floors/stairs require a minimum of four coats (any sheen level).

Clean Up

Wash with soap/mild detergent and water

Coverage

Smooth wood: 350-400 square feet per gallon.
Rough wood: 250-300 square feet per gallon.
Hardwoods: 350-400 square feet per gallon.
Note: Coverage will vary with the porosity of the wood.

THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Log+Siding
Ultra DF
Roof Treatment
Yard Treatment

Ultra LS
Crystal Urethane
Strip+Brite
EZ PRO

Deck+Fence
Timber Seal
Interior Stain Formula

XP
Clean+Brite

Timber Pro Coatings Canada

Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

www.TimberProCoatings.ca
www.TimberProCoatings.com