

EZ PRO

EZPRO



FEATURES:

- **EXCELLENT PENETRATION:** EZ PRO allows for penetration into the wood surface.
- **EXCELLENT UV PROTECTION:** Unique UV absorbers and enhanced micronized pigments protect the wood from the sun's UV rays.
- **LOW VOC. FORMULA:** EZ PRO is not harmful to the environment.
- **SUITABLE FOR UNSEASONED WOOD:** The unique formula allows for use on wood with higher moisture content (21% or less).
- **BREATHABLE FINISH:** EZ PRO breathability reduces moisture build-up in wood and stabilizes wood to reduce warping and checking.
- **EASY TO APPLY:** EZ PRO can easily be applied by brush or sprayed and back brushed.
- **EASY TO MAINTAIN:** The unique formula does not peel, flake or blister; no sanding is required prior to the maintenance coat. Simply wash the surface, let dry and apply a single application of EZ PRO to keep the wood surface protected and beautiful.
- **EASY CLEAN UP:** Soap and water clean up.

EZ PRO

Protects + Beautifies:

Timber Pro EZ Pro is a unique waterborne resin formula designed to stand up to the harshest environments.

EZ Pro uses a unique combination of sunscreens and pigments that protects the wood surface from the sun's UV rays. EZ PRO provides a durable breathable finish to beautify and protect your wood surface from day-to-day use and wear, as well as from the elements. Designed as a "one coat" protection system, an additional coat would offer extended maintenance cycles as well as increase protection to wood surfaces.

604.270.4244

timberprocoatings.ca

timberprocoatings.com

DEALER STAMP



EZ PRO

Protects + Beautifies

Where to Use

Timber Pro EZ PRO can be used on all new and reconditioned wood exterior and interior surfaces. EZ PRO can be used on wood species such as cedar, fir, pine, cypress, redwood, spruce exterior-grade plywood, pressure treated and Thermally Modified Wood. EZ PRO can be used for:

- Decks
- Outdoor Furniture
- Fences
- Siding
- Gazebos
- Logs
- Pergolas

RESTRICTIONS

- Always use a colour coat before the clear coat (if a second coat was desired or required)
- Always read and follow the "Directions for Use" instructions printed on the product container/brochure and/or on website www.timberprocoatings.ca
- Do not apply in direct sunlight or in temperatures below 10C (50F) and above 25C (80F).
- Do not apply on surfaces hot to the touch
- Do not thin the product
- Do not apply over previously coated surfaces

Application

- Do a colour test before proceeding with the entire job.
- Apply one saturated coat of colour; a second coat can be applied if desired, the second coat can be pigmented or clear
- Check the moisture content of wood. Apply coating when surface moisture content is less than 21%.
- Stir the material thoroughly before and occasionally during use.
- Application is best with a quality nylon/polyester brush or with an airless sprayer and back brushed immediately after.
- Apply two coats of colour; it is extremely important to allow each coat to dry before proceeding with the next coat.
- Wood may be pre-finished with one or two coats of EZ Pro before installation. Back priming is recommended.
- Generously coat the surface and all exposed end grain. Apply as liberally as possible without runs. Do not try to stretch coverage. Apply in the direction of the grain. On rough-sawn surfaces, thoroughly saturate and back brush to soak as much product as possible into the wood. If spraying, spray until the product runs slightly and then immediately back brush. Avoid lap marks by starting at one end of a given surface and while maintaining a wet edge, follow through to the opposite end of the surface area. It is extremely important to allow each coat to dry before proceeding with the next coat if desired or required.

Clean Up

Wash with soap/mild detergent and water.

Coverage

Smooth wood: 250-300 square feet per gallon.
Rough wood: 150-200 square feet per gallon.
Hardwoods: 300-350 square feet per gallon.
Note: Coverage will vary with the porosity of the wood.

THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Log+Siding
Ultra DF
Roof Treatment
Yard Treatment

Ultra LS
Crystal Urethane
Strip+Brite
EZ PRO

Deck+Fence
Timber Seal
Interior Stain Formula

XP
Clean+Brite

Timber Pro Coatings Canada
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

www.TimberProCoatings.ca
www.TimberProCoatings.com