



TP EZ PRO CLEAR

DESCRIPTION

Timber Pro EZ Pro Clear is a 100% acrylic coating designed for use on exterior wood surfaces. This product comes in clear and translucent and provides beauty and protection with wood grain visibility while ensuring optimal UV protection to help preserve the natural beauty of wood and is a nonhazardous and ecologically sound product with extremely low emissions (Low VOC's).

ADVANTAGES

- UV Resistant
- Impact Resistant
- Flexible

PACKAGING

- US 5 Gallon Pail;
- US Gallon Can;
- US Quart Container.

Coverages

Coverages given are approximate and will vary depending on substrate, details, and individual application technique.

PREPARATION

In cool / moist conditions cure times longer than the recommended 24 hours might be needed.

Surface must be fully cured, dry and free of dust prior to application.

Mixing

Ready to use

Characteristics

Gloss	13-18
% Volume solids	20%
Viscosity-sec	18-22
WPG	8.7

Recommended film thickness

Mils Wet	2.0-4.0
Mils Dry	0.64-1.6
Spreading Rate DFT	260-370 sq.ft.
Drying 77°F @RH 50%	
VOC gms/L	<50g
To touch	5 minutes
To handle	15 minutes

Spray or Brush

To recoat	Same day
	Air Dry

**Typical Setup Airless
Spray:**

Fluid Pressure	1400-2400 psi
Tip size	0.008-0.015

Air Assisted Airless:

Air pressure	10-20 psi
Fluid pressure	500-800 psi
Tip size	0.008-0.015

HVLP- Pressure Feed:

Air Inlet Pressure	20-30 psi
Fluid pressure	5-10 psi
Tip size	1.4-1.8

Clean up: warm soapy water

Product Data Sheets are periodically updated to reflect new information related to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, ratings and opinions stated above pertain to the material currently offered and represent the results of tests believed to be reliable. However due to variations in customer handling and methods of application, which are not known, or under our control. Timber Pro Coatings Ltd cannot make any warranties or guarantees as to the end results .

Revision date October 01st 2021

Timber Pro Coatings Ltd

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4

Ph: 604-270-4244 Fax: 604-270-4247; Toll Free: 1-877-666-4244; Email: canadainfo@timberprocoatings.ca